

# strapex

## SMG 10/15/25

### High performance machines for plastic strapping

**NEW**



SMG 10/15



SMG 25



New technology  
allows use of thin or  
narrow strap



**Save time and money with 5 mm plastic strap!**

# SMG 10/15/25

## For small to large packages


### 5 Highlights

- Up to 70 cycles per minute
- Touch Panel: Strap tension easily adjustable
- Simple technology, few moving parts
- Constant strap tension for various products
- Simple coil change

### Cost effective

- High availability
- Use of 5 mm PP strap with SMG 10 – the alternative to 9/12 mm strap
- Use of thin PP straps
- Maintenance-friendly


### Strapex advantage



Machine, strap and after-sales service as a total package

### User friendly

- Plug & Play: Very easy handling
- Mobile, ready to use anywhere
- Adjustable working height
- All operating functions using foot pedal



Strap tension easily adjustable with press button



Simple coil change



Easily accessible



Maintenance without tools



Robust, compact design

### Options




Second foot pedal for operation on both sides



Cycle start triggered by photocell



Roller table for easy handling of heavy parcels



Bundle stops for precise positioning of loose packages

### Further options

- **CT-Version (Cold and Tropic Environment)**
- **Foot switch with protection cover**
- **Hold down device** for compressing loose packages
- **Interface** for integration into existing production plants

Technical data	SMG 10	SMG 15	SMG 25
Dispenser position	Integrated	Integrated	Side mounted
Performance per minute	70 cycles	65 cycles	60 cycles
Arch dimensions (width x height)			
– 500 x 400 mm	5/6 mm		
– 650 x 500 mm	5/6 mm	9/12 mm	
– 850 x 650 mm			9/12 mm
– 850 x 850 mm			9/12 mm
– 1250 x 500 mm			9/12 mm
– 1250 x 850 mm			9/12 mm
– 1550 x 500 mm			9/12 mm
Working height	820–930 mm	820–930 mm	820–930 mm
– Option			670–830 mm
Electrical supply	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz
Strap tension, up to	300 N	450 N	450 N
Seal	Heat seal	Heat seal	Heat seal
Weight	170 kg	170 kg	190 kg
<b>Plastic strap (PP)</b>			
Width 5 mm	372.605.585		
9 mm		371.609.555	371.609.555
12 mm		371.612.540	371.612.540
Strap coil, inside/outside Ø	200/430 mm	200/430 mm	200/430 mm
<b>Packages</b>			
Min. width / Max. weight	100 mm / 35 kg	100 mm / 35 kg	100 mm / 35 kg

**U.K.**  
Strapex  
Unit 50  
Empire Industrial Park  
Empire Close  
Aldridge, Walsall, WS9 8UQ  
Phone +44 1922 742 500  
Fax +44 1922 742 501

**Denmark**  
ApS Strapex  
Literbuen 9  
2740 Skovlunde  
Phone +45 44 85 06 00  
Fax +45 44 84 94 22

**Holland**  
Strapex Nederland B.V.  
Sterrebaan 10  
3542 DK Utrecht  
Phone +31 30 24 80 311  
Fax +31 30 24 11 654

**USA**  
Acme  
An ITW Company  
501 W. Lake Street, Suite 105  
Elmhurst, IL 60126  
Phone 630-589-5100  
Fax 630-589-5101

**Australia**  
IWD Strapping Sales Pty Ltd.  
P.O. Box 215  
Melbourne Vic 3001  
Phone 1 800 779 380  
Fax 1 800 779 583

**India**  
Strapex India Limited  
506, Center Point, J.B. Nagar  
Andheri-Kurla Road, Andheri (E)  
Mumbai - 400 059  
Phone +91-22-66400204/05  
Fax +91-22-28252932